

HEXAMOTIONTM



Tender specification

always the best climate

- HEXAMOTION™, compact self-regulating energy recovery unit, for indoor installation on the floor and outdoor installation with its integrated roof, high efficiency 80%.
- EUROVENT N°21.03.72 (L1(M) [-400Pa]/D2/T3/TB3/F9) certified range, ErP2018 compliant.
- MODBUS, BACNET or WEB communicating.
- Self-supporting structure, double-skin RAL9007 exterior, insulated with 50mm M0 high-density mineral wool (60 kg/m3).
- Fitted with a variable speed rotary exchanger, available in S version with SORPTION wheel for optimal hygrothermal management, F7 ePM1 55% (fresh air) and M5 ePM10 50% (extracted air) filters mounted on a sealed slide (optional double filtration stage on fresh air for F7+M5/F9), free-cooling and night-cooling (except SEASON), 3 integrated sensors.
- Pure technology CLEARMOTION™, innovative, patented solution and éconologic™ to decontaminate,
 depollute and disinfect air and surfaces for a Very High Indoor Air Quality.
- **FEE™** (Free Energy Efficiency), a 3-way module upstream of the unit for an all-season econologic™ optimisation of the building's energy needs.
- Available in 3 versions (SEASON, FIRST, PREMIUM), the HEXAMOTION™ unit can integrate an electric, water changeover or direct expansion heating coil.
- Very low consumption EC motorised fans.
- Lockable mains power cut-off switch and LCD remote control (optional) except for the SEASON version, which is fitted with 2 potentiometers.
- Dual seal round spigots to guarantee airtightness of networks (ATEC CSTB n° 13-224-V2).
- Fire safety function (except SEASON) to control supplied and extracted air fans.
- 100% PLUG&PLAY range.